

## **Product Specification - PARAFFINIC OIL**

### **Paraffinic Oil 60**

<b>Specification</b>	<b>Test Method</b>	<b>Unit Measurement</b>	<b>Min</b>	<b>Max</b>
Specific Gravity at 60/60 F	ASTM D-1298		0,864	0,8735
Viscosity Kinematic at 210 F	ASTM D-445	Cst	4,5	5
Viscosity Gravity Constant	ASTM D-2501		0,8095	0,8205
Refractive Index at 20 C	ASTM D-1218		1,475	1,4815
Pour Point	ASTM D-97	°C	-	8
Flash Point C.O.C	ASTM D-92	°C	400	-
Colour ASTM 1% dilution	ASTM D-1500		-	0,5
Aniline Point	ASTM D-611	°C	96	103

### **Paraffinic Oil 60**

<b>Specification</b>	<b>Test Method</b>	<b>Unit Measurement</b>	<b>Min</b>	<b>Max</b>
Specific Gravity at 60/60 F	ASTM D-1298		0,876	0,885
Viscosity Kinematic at 210 F	ASTM D-445	Cst	6,9	7,6
Viscosity Gravity Constant	ASTM D-2501		0,81	0,833
Refractive Index at 20 C	ASTM D-1218		1,48	1,49
Pour Point	ASTM D-97	°C	-	15
Flash Point C.O.C	ASTM D-92	°C	410	-
Colour ASTM 1% dilution	ASTM D-1500		-	0,5
Aniline Point	ASTM D-611	°C	100	109